


Festkupplungen mit Außengew. NPT, NH, NPSH, NSW
Adapters with male thread NPT, NH, NPSH, NSW



Dichtung: Nitril-Kautschuk schwarz / weiß
 Viton Dichtung bei V4A

Seal: Nitrile rubber black / white
 Fluoro rubber - Stainless steel



Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------

Storz Size	KA (mm) Lug	Außengewinde Male thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
25-D	31	3/4" NPT	0,06		22-031075-19	
		3/4" NPT	0,19		22-031075-39	
		1" NPT	0,08		22-031100-19	
		1" NPT	0,22		22-031100-39	
		1" NPT	0,21		22-031100-49	
		1" NH	0,07		22-031100-18	
		1" NPSH	0,07		22-031100-17	
38	51	1 1/4" NPT	0,15		22-051125-19	
		1 1/2" NPT	0,14		22-051150-19	
		2" NPT	0,16		22-051200-19	
		1 1/2" NH	0,15		22-051150-18	
		1 1/2" NPSH	0,14		22-051150-17	
52-C	66	1 1/2" NPT	0,26		22-066150-19	
		2" NPT	0,23		22-066200-19	
		2" NPT	0,84		22-066200-39	
		2 1/2" NPT	0,25		22-066250-19	
		1 1/2" NH	0,24		22-066150-18	
		1 1/2" NH	0,86		22-066150-38	
		2 1/2" NH	0,24		22-066250-18	
		1 1/2" NPSH	0,25		22-066150-17	
		2" NPSH	0,21		22-066200-17	
2 1/2" NPSH	0,24		22-066250-17			
65	81	2" NPT	0,36		22-081200-19	
		2 1/2" NPT	0,35		22-081250-19	
		3" NPT	0,33		22-081300-19	
		2 1/2" NH	0,39		22-081250-18	
		2 1/2" NH	1,16		22-081250-38	
		3" NH	0,34		22-081300-18	
		5 1/5 NSW	0,38		22-081520-10	

Festkupplungen mit Außengew. NPT, NH, NPSH, NSW
Adapters with male thread NPT, NH, NPSH, NSW



Storz Size	KA (mm) Lug	Außengewinde Male thread	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
65	81	2 " NPSH	0,36		22-081200-17	
		2½ " NPSH	0,35		22-081250-17	
		3 " NPSH	0,33		22-081300-17	
75-B	89	2 " NPT	0,39		22-089200-19	
		2½ " NPT	0,35		22-089250-19	
		3 " NPT	0,38		22-089300-19	
		2½ " NH	0,35		22-089250-18	
		2½ " NH	1,20		22-089250-38	
		3 " NH	0,39		22-089300-18	
		2 " NPSH	0,40		22-089200-17	
		2½ " NPSH	0,35		22-089250-17	
		3 " NPSH	0,39		22-089300-17	
100	115	4 " NPT	0,74		22-115400-19	
		2½ " NH	1,30		22-115250-18	
		3 " NH	1,20		22-115300-18	
		4 " NH	0,85		22-115400-18	
		4½ " NH	1,30		22-115450-18	
		5 " NH	1,75		22-115500-18	
		6 " NH	1,90		22-115600-18	
		4 " NPSH	0,71		22-115400-17	
110-A	133	4 " NPT	1,08		22-133400-19	
		4 " NH	1,05		22-133400-18	
		4 " NPSH	1,01		22-133400-17	
125	148	5 " NPT	1,81		22-148500-19	
		2½ " NH	1,95		22-148250-18	
		3 " NH	1,90		22-148300-18	
		4 " NH	1,75		22-148400-18	
		4½ " NH	1,30		22-148450-18	
		5 " NH	2,00		22-148500-18	
		6 " NH	2,25		22-148600-18	
150	160	6 " NPT	2,24		22-160600-19	

NPT = Kegeliges Rohrgewinde 60°
Taper Pipe Thread acc. ANSI B 1.20.1-1983 (USA)

NH = Zylindrisches Gewinde 60°
NST National Standard Thread for fire hose connections acc. NFPA 1963 (USA)

NPSH = Zylindrisches Rohrgewinde 60°
Standard Straight Hose Coupling Thread acc. ANSI B 2.4-1966 (USA)